

AD-A087 878

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OH

F/6 9/1

COMMUTATOR, (U)

DEC 79 P N DASHUK

FTD-ID(RS)T-1851-79

UNCLASSIFIED

NL

1 of 1
AD-A087 878



END

DATE

FILED


9-80

DTIC

PHOTOGRAPH THIS SHEET

ADA 087878

DTIC ACCESSION NUMBER



LEVEL



INVENTORY

FTD-ID(RS)T-1851-79
DOCUMENT IDENTIFICATION


DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

DISTRIBUTION STATEMENT

ACCESSION FOR	
NTIS	GRA&I <input checked="" type="checkbox"/>
DTIC	TAB <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION /	
AVAILABILITY CODES	
DIST	AVAIL AND/OR SPECIAL
A	

DISTRIBUTION STAMP



DATE ACCESSIONED

80 6 2 237

DATE RECEIVED IN DTIC

PHOTOGRAPH THIS SHEET AND RETURN TO DTIC-DDA-2

ADA 087878

FTD-ID(RS)T-1851-79

FOREIGN TECHNOLOGY DIVISION



COMMUTATOR

by

P. N. Dashuk



Approved for public release;
distribution unlimited.



EDITED TRANSLATION

FTD-ID(RS)T-1851-79

11 December 1979

MICROFICHE NR: FTD-79-C-001582

CSP72057794

COMMUTATOR

By: P. N. Dashuk

English pages: 3

Source: USSR Patent Nr. 319973, 2 September 1971,
pp. 1-2

Country of Origin: USSR

Translated by: Victor Mesenzeff

Requester: FTD/TQTD

Approved for public release; distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP. AFB, OHIO.

U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	А а	A, a	Р р	Р р	R, r
Б б	Б б	B, b	С с	С с	S, s
В в	В в	V, v	Т т	Т т	T, t
Г г	Г г	G, g	У у	У у	U, u
Д д	Д д	D, d	Ф ф	Ф ф	F, f
Е е	Е е	Ye, ye; E, e*	Х х	Х х	Kh, kh
Ж ж	Ж ж	Zh, zh	Ц ц	Ц ц	Ts, ts
З з	З з	Z, z	Ч ч	Ч ч	Ch, ch
И и	И и	I, i	Ш ш	Ш ш	Sh, sh
Й й	Й й	Y, y	Щ щ	Щ щ	Shch, shch.
К к	К к	K, k	Ъ ъ	Ъ ъ	"
Л л	Л л	L, l	Ы ы	Ы ы	Y, y
М м	М м	M, m	Ь ь	Ь ь	'
Н н	Н н	N, n	Э э	Э э	E, e
О о	О о	O, o	Ю ю	Ю ю	Yu, yu
П п	П п	P, p	Я я	Я я	Ya, ya

*ye initially, after vowels, and after ъ, ь; e elsewhere.
When written as ě in Russian, transliterate as yĕ or ě.

RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English	Russian	English	Russian	English
sin	sin	sh	sinh	arc sh	sinh ⁻¹
cos	cos	ch	cosh	arc ch	cosh ⁻¹
tg	tan	th	tanh	arc th	tanh ⁻¹
ctg	cot	cth	coth	arc cth	coth ⁻¹
sec	sec	sch	sech	arc sch	sech ⁻¹
cosec	csc	csch	csch	arc csch	csch ⁻¹

Russian English

rot curl
lg log

COMMUTATOR

P. N. Dashuk

Leningrad Polytechnical Institute im. M. I. Kalinin

This invention pertains to the gas-discharge commutators used primarily in capacitive accumulators of energy of the electro-physical installations.

There are gas-discharge commutators containing a gas-discharge dielectric chamber, at least two electrodes located in the chamber one opposite the other, and contact conductors located outside the chamber and electrically connected with the electrodes.

The construction of the external insulation of the discharge chambers does not permit the current-supplying buses to come close to one another directly at the discharger, which results in an increase in the inductivity of the circuit and, in the case of high operating voltages of the accumulator, considerable difficulties arise in ensuring the necessary electrical strength at the point where the insulation of the discharger comes in contact with the insulation of the external electrical buses.

In the commutator being proposed the side walls of the discharge chamber are made out of block polyethylene with the sheets of polyethylene film welded to it. Such a design of the gas-discharge commutator makes it possible to ensure high electrical strength of the external insulation of the discharge chamber and low inductance of the current feeds to the discharger.

The drawing shows a schematic representation of the external view of a gas-discharge commutator.


The device consists of the base electrodes 1, ignition electrodes 2, discharge chamber 3 made out of a monolithic polyethylene and sheets of polyethylene film which are welded to the external surface of the chamber along the generatrix. Current-supplying buses 5 are separated by insulation 6, sheets of film dielectric.

When voltage is fed to the electrodes of the discharger, high electrical strength of the external insulation of the device is ensured due to the high electrical strength of several serially-arranged seams of the film welded to the external surface of the chamber, despite the small distance between the electrodes. In view of the fact that it is convenient to weld the film polyethylene with the block polyethylene only at the spots where the surface of the block polyethylene parallels the surface of the film or is at a small angle to it, it is expedient to make sloping sections on the external surface of the discharge chamber and weld a sheet of film to each one individually for which similar holes were cut in the sheets with a perimeter, which decreases from sheet to sheet.

The external surface of the discharge chamber can be made differently, which is also convenient for welding the film polyethylene. In this case, steps are made on the external surface of the discharge chamber to match the number of sheets of the polyethylene film.

Object of the invention

The commutator containing a discharge dielectric chamber, at least two electrodes, and contact conductors located outside the chamber and which are electrically connected with the electrodes is distinguished by the fact that in order to decrease the inductance of the commutator, the side walls of the discharge chamber are made out of block polyethylene with sheets of polyethylene film welded to it.



DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

<u>ORGANIZATION</u>	<u>MICROFICHE</u>	<u>ORGANIZATION</u>	<u>MICROFICHE</u>
A205 DMATC	1	E053 AF/INAKA	1
A210 DMAAC	2	E017 AF/RDXTR-W	1
B344 DIA/RDS-3C	9	E403 AFSC/INA	1
C043 USAMIIA	1	E404 AEDC	1
C509 BALLISTIC RES LABS	1	E408 AFWL	1
C510 AIR MOBILITY R&D	1	E410 ADTC	1
LAB/FIO			
C513 PICATINNY ARSENAL	1	FTD	
C535 AVIATION SYS COMD	1	CCN	1
C591 FSTC	5	ASD/FTD/NIIS	3
C619 MIA REDSTONE	1	NIA/PHS	1
D008 NISC	1	NIIS	2
H300 USAICE (USAREUR)	1		
P005 DOE	1		
P050 CIA/CRB/ADD/SD	2		
NAVORDSTA (50L)	1		
NASA/NST-44	1		
AFIT/LD	1		
ILLI/Code L-389	1		
NSA/1213/TDL	2		